

Cement Filler SIL-A

Chemical filler based on methasilicate compounds, used to obtain lightweight cement mortars.

An economic solution that allows to reduce the density of cement mortar due to the addition of water.

It has a side effect of the setting accelerator, which contributes to an early set of strength lightweight cement mortar.

It can be used for the preparation of a clogging pack in conjunction with saturated CaCl₂ solutions.

Advanteges

- Binds excess cement slurry water. Reduces water separation.
- Added to dry cement mix.
- Promotes an early set of strength.
- High solubility in water.
- Can be used with other fillers.

Technical Parameters

| Description | Specification |
|---|--------------------------------|
| Appearance | Granulated white powder |
| Working concentration | 0.25 - 3.5% (BWOC) |
| Cement slurry dencity, gr/cm ³ | 1.45 - 1.70 gr/cm ³ |

Tel:
+7495 3202820

E-Mail:
info@3spolymers.ru

3S POLYMERS LTD

INN 3851018522
OGRN 1163850095001
665830 Russia, Irkutsk
Region., Angarsk,
Moscowskaya st, 19

ООО "ЗС ПОЛИМЕРС"

ИНН 3851018522
ОГРН 1163850095001

665830 Россия,
Иркутская Обл.,
г. Ангарск,
ул. Московская 19

Packing, transportation, handling

- 3-layer 25kg bags or under customer's request
- Keep in closed packing in dry and well ventilated places
- Do not damage packing.
- Shelf time 2 years.