

### Liquid defoamer CleanSol

CleanSol Liquid Defoamer belongs to the proven polyester defoamer group.

The defoamer is universal and can be used in the preparation of cement mortars, buffer fluids, acid systems, hydraulic fracturing fluids and drilling fluids.

The product has a low freezing temperature of -50 g C and can be used in the Far North.

CleanSol is applicable both to prevent foaming and to break down existing foam.

#### Advantages

- CleanSol is a high molecular weight polyester compound.
- Colorless liquid with a density of 0.9-1.0gr / cm<sup>3</sup> Odorless.
- Non-corrosive, non-toxic, environmentally friendly.
- Effective in fresh and saline solutions.
- Compatible with other additives.
- Does not affect other properties of process fluids.
- 

#### Technical parameters

Description	Specification*
Concentration	0.1% - 0.3% (BWOC)
Foam decreasing rate,%	≥99.0

\* Cement G, density 1.9 gr/cm<sup>3</sup>, CleanSol 0.3% fresh and salt (NaCl) water.

#### Packing, transportation, handling

- 25kg, 200kg drums or under customer request
- Keep in closed packing in dry and well ventilated places
- Do not damage packing.
- Shelf time 1 year.

Tel:  
+7495 3202820

E-Mail:  
info@3spolymers.ru

3S POLYMERS LTD

INN 3851018522  
OGRN 1163850095001  
665830 Russia, Irkutsk  
Region., Angarsk,  
Moscowskaya st, 19

ООО "ЗС ПОЛИМЕРС"

ИНН 3851018522  
ОГРН 1163850095001

665830 Россия,  
Иркутская Обл.,  
г. Ангарск,  
ул. Московская 19