

Solid CleanSol-S

Dry antifoam CleanSol-S belongs to the proven polyester defoamer group.

The defoamer is universal and can be used in the preparation of cement mortars, buffer fluids, acid systems, hydraulic fracturing fluids and drilling fluids.

The product is a dry powder and can be added to the cement mixture.

CleanSol-S is applicable both to prevent foaming and to destroy existing foam.

Advantages

- CleanSol-S is a high molecular weight polyester compound.
- Powder with a density of $1.45 \pm 0.03 \text{ g / cm}^3$
- Non-corrosive, non-toxic, environmentally friendly.
- Effective in fresh and saline solutions.
- Compatible with other supplements.
- Does not affect other properties of process fluids.

Technical Parameters

Description	Specification*
Working concentration	0.1% - 0.3% (BWOC)
Foam decreasing rate, %	≥ 99.0

* Cement G, density 1.9 gr/cm^3 , CleanSol-S 0.3 fresh and salt (NaCl) water.

Packing, transportation, handling

- 3-layer 25kg bags or under customer's request
- Keep in closed packing in dry and well ventilated places
- Do not damage packing.
- Shelf time 2 years.

Tel:
+7495 3202820

E-Mail:
info@3spolymers.ru

3S POLYMERS LTD

INN 3851018522
OGRN 1163850095001
665830 Russia, Irkutsk
Region., Angarsk,
Moscowskaya st, 19

ООО "ЗС ПОЛИМЕРС"

ИНН 3851018522
ОГРН 1163850095001

665830 Россия,
Иркутская Обл.,
г. Ангарск,
ул. Московская 19