

Washing buffer WellFlush OBM

WellFlush OBM is a washing buffer designed for dissolving and washing the filter cake of the drilling fluid at the CBM from the wellbore, as well as washing the film of drilling fluid at the CBM from the surface of the casing. Using a washing buffer allows you to change the wettability of the surface to hydrophilic and increase the adhesion of cement and, as a result, improve the quality of the well attachment.

Advantages

- Specially selected composition of surfactants and solvents
- Non-toxic, non-corrosive, odorless
- Working concentration from 3% to 25% by weight of water
- Operating temperature from 15 °C to 140 °C, circulation temp. (BHCT)

Technical parameters

Description	Specification*
Appearance	Transparent liquid
Specific weight, gr/cm ³	0.98 - 1.04
pH	7 - 9
Washing capacity, %	≥ 80

*15% solution, contact time 10мин at rom temperature

Packing, transportation, handling

- 25kg, 200kg drums or under customer request
- Keep in closed packing in dry and well ventilated places
- Do not damage packing.
- Shelf time 1 year.

Tel:
+7495 3202820

E-Mail:
info@3spolymers.ru

3S POLYMERS LTD

INN 3851018522
OGRN 1163850095001
665830 Russia, Irkutsk
Region., Angarsk,
Moscowskaya st, 19

ООО "ЗС ПОЛИМЕРС"

ИНН 3851018522
ОГРН 1163850095001

665830 Россия,
Иркутская Обл.,
г. Ангарск,
ул. Московская 19